

शंखरापुर नगरपालिका नगर कार्यपालिकाको कार्यालय साँखु, काठमाडौँ बागमती प्रदेश, नेपाल



क्याटलग/ब्रोसर सपिङ विधिबाट ब्याकहो लोडर खरिद सम्बन्धी सूचना

(प्रथम पटक प्रकाशित मितिः २०८१/०८/११)

सार्वजनिक खिरद ऐन, २०६३ को दफा ८ को उपदेफा (१) खण्ड (क) को देहाय (८) तथा सार्वजनिक खिरद नियमावली २०६४ को नियम ३१ (ख) बमोजिम सवारी साधन उत्पादन गर्ने कम्पनी वा सोको आधिकारिक बिक्रेताहरू बीच प्रतिस्पर्धा गराई क्याटलग सिप्ड विधिबाट ब्याकहो लोडर खिरद गर्नुपर्ने भएकोले इच्छुक इजाजत प्राप्त उत्पादक कम्पनी वा त्यसको आधिकारिक विक्रेताहरूले आफ्नो फर्म दर्ता प्रमाण-पत्र, मु.अ.कर दर्ता प्रमाण पत्र, एजेन्सी दर्ता प्रमाण पत्र र आ.व. २०८०/८१ को कर चुक्ताको प्रतिलिपि समावेश गरी सार्वजनिक खिरद नियमावली, २०६४ को नियम ३१ ख को उपनियम (२) अनुसार देहाय बमोजिमको सवारी साधनको उत्पादक वा आधिकारिक विक्रेताले स्पेशिफिकेशन, गुणस्तर, कम्पनीको मुल्य खुल्ने कागजात र सुविधा सिहतको विवरण क्याटलग/ब्रोसर संलग्न गरी सूचना प्रकाशित भएको मितिले ७ (सात) दिनभित्र यस कार्यालयमा निवेदन दर्ता गर्नुहुन सम्बन्धित उत्पादक वा आधिकारिक विक्रेताको जानकारीको लागि यो सूचना प्रकाशित गरिएको छ। निवेदन दर्ता गर्ने अन्तिम दिन विदा परेमा त्यस दिनपछिको कार्यालय खुल्ने दिन दर्ता गर्न सिकिनेछ।थप जानकारीका लागि कार्यालयमा सम्पर्क गर्नुहुन अनुरोध छ।

क्र. सं.	सवारी साधन	विवरण	परिमाण
1	(Backhoe	Four Wheel drive, Operating weight 8000 kg +-10%, loader Multipurpose (6 in 1to facilitate dozing, digging, grading, backfilling, grabbing, and loasing) bucket not less than 1 cum, water cooled diesel engine power not less than 90 HP, maximum Torque not less than 390 N-M, hydraulic system pressure not less than 220 bar, maximum pump flow not less than 115 LPM, axle 4wd with fixed rear axle and oscillating front axles.(For more details of specification contact to office or visit website)	1

सम्पर्कः

शंखरापुर नगरपालिका, साँखु, काठमाडौँ

shankharapur.municipality@gmail.com, www.shankharapurmun.gov.np, सम्पर्क नं. 01-4450355

Technical Specifications

S.N	. CRITERIA	REQUIREMENT	1 Nos
1	General		OFFERED
'	General	Four wheel drive, rigid frame backhoe loader with steel cab, suitable for at energial conditions and adverse at	SPECIFICATION
		operation under rough working conditions and adverse climatic condition at operating altitude ranging from 80 m to 2500 m (m, l)	ONTON
		at Operating altitude remains of adverse climatic against	
2	Capacity / Size	temperature varying between 100 = 2500 iii (msl) and omt	
_	Cupacity / Size		
		grading, backfiling, grabbing and loading application) bucket than Leum.	
		with bolt on teeth of SAE rated constitution application) bucket	
		with bolt on teeth of SAE rated capacity nominally heaped: Not less Shovel break and s	
		Shovel break out force: Not less than 5250 kgf Maximum dumping height: Not less than 5250 kgf	
		Maximum dumping height: Not less than 5250 kgf Backhoe: Backhoe bucket with holt on to the	
		3. Backhoe: Backhoe bucket with balk	
		U.3 Cil. m +100/	
		Bucket break out force: Not less than 5400 kgf Maximum working height: Not less than 5400 kgf	
		Maximum working height: Not less than 5400 kgf Maximum digging depth: Not less than 6000 mm	
		Maximum diggin. Not less than 6000 mm	
		Maximum londons 1 1100 less than 4800 mm	
		Maximum diagong reach: Not less than 4000 mm level to rear wheel centre) To be equipment.	
		level to rear wheel	
3	Parent	- o be equilibred with and t	
3	Engine	Water cooled Disselve Water controls from cabin	
		Water cooled, Diesel engine, developing Maximum Gross Power not less than 90 HP (engine fully equipped with accessor)	
		less than 90 HP (engine fully equipped with accessories) at governed RPM and Maximum Torque not less than 390 N-m for efficient full load operation of backhoe loader at operating conditions as extended	
		Operation of backless of less than 390 N-m for efficient 6 lbs	
		operation of backhoe loader at operating conditions as stated in the bid	
		document. Backhoe loader shall be equipped with heavy duty radiator,	
		cold starting device, direct electric starting system, heavy duty air cleaner, heavy duty fuel filter with water tree.	
		heavy duty air cleaner, heavy duty fuel filter, with water trap and drainage	
4	Transmission	in fuel line and drain tap in fuel tank.	
5	Axles	- 5. que converier with for	
6	Steering	Four wheel drive with fixed rear axle and oscillating front axles.	
7	Brakes	Hydraulian Hydraulian	
		Hydraulically actuated, wet multiple disc/caliper disc type service brake	
8	Hydraulics	and separate parking brake	
	y and arrives	Suitable hydraulic system for smooth operation of all attachments Hydraulic System Pressure: Not less than 220 P.	
		Hydraulic System Pressure: Not less than 220 Bar	
9	Cab	Maximum pump flow: Not less than 220 Bar All steel enclosed FORM	
	Cuo		
		roof, suitably located controls for back hoe (excavator) and loader operation, rear view mirror, cabin light, wiper and editors and loader	
		operation, rear view mirror, cabin light, wiper and adjustable cushioned	
0		seat for operator shall be provided	
0	Essential	1. Road lights, work lights and fog lights	
	Accessories	2. Cabin lights	
		3. Service hour meter	
		Equipped with all assess is as	
		Equipped with all accessories offered in standard model but not limited to the above items.	
	Instructions		
	Manuals	All signs and instructions in the equipment shall be in English	
	anuals	T. One copy of the Operator's and Owner's Instructions and Maintenant	
		manual in English shall be supplied with each equipment	
		2. Eight copies of following manuals in English shall be supplied with	
		equipments:	
		Spare parts catalogue	
		Comprehensive workshop manual	
Т	ools	A set of tools included by the transfer	
1	0015	A set of tools including hydraulic jack with handle as required for genera	1
		maintenance shall be supplied with in a lockable tool box/tool bag for	r
		each unit	
H	arranty	Manufacturer shall provide a minimum of one year warranty after	\r
1 ,,		and all the state of the provide a minimum of one year warranty and	1 (

Jufe 15

	The supplier shall provide all necessary filters, lubricants and spare parts including lubricants with the equipment, required for the first three services, after the equipment has been commissioned and accepted	
17 Delivery	The Backhoe Loader, 1 unit—shall be delivered to following places in Nepal: Sankarapur, Municipality, Saakhu, Kathmandu, Nepal.	

Note:

- a) The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in non-responsiveness of the bid offer as per ITB 31.3.
- The bidder must submit documentry evidences/ manufacturer declaration showing that he/she meets all the requirements as mentioned in Section III, Evaluation and Qualification Criteria.

(Prem Prasad Rigal)